



GRAFFITI

LED downlights include round/flanged, round flangeless, square/flanged, and square flangeless profiles.

US tested to UL standards 1598, dry/damp and wet listings.

Title 24, JA8 compliant.

**ST option available, wet listed for showers and steam rooms.

Finish: Black powder paint housing; Trim available in white as standard – can be field painted to match ceiling finish.

DETAILS.

SIZE:

ROUND/FLANGED- 5" DIA.

ROUND/FLANGELESS- 6 1/4" DIA.

SQUARE/FLANGED- 5" X 5"

SQUARE/FLANGELESS- 5 1/2" X 5 1/2"

0-10V DIMMING, 1%, 120-277V

COLOR, CRI 90+:

2700K, 3000K, 3500K, AND 4000K

BEAM OPTIONS:

SP- SPOT (15°)

NF- NARROW FLOOD (24°)

F- FLOOD (38°)

WF- WIDE FLOOD (60°)

LAMP OPTIONS:

CZ- CITIZEN 2700-4000K, 90+CRI

AD- AMBIENT DIMTM 3000-1900K, 97 CRI

XT- XICATO 2700-4000K, 90+ CRI

LENS:

91A- SOLITE OR 79A- FROSTED

HOUSING TYPES:

RM - RETROFIT

IC - IC

NIC - NEW CONSTRUCTION, IC NOT REQUIRED

NP - NEW CONSTRUCTION

DP - DROPPED PAN

BP - BRACKET PAN

CP - CHICAGO PLENUM

DRIVERS:

STANDARD




TRIAC/ELV

LUTRON HI-LUME

ELDOLED

UL LISTED, TITLE 24, JA8 COMPLIANT

GRAFFITI



AFFORDABLE AMBIENCE

Graffiti represents a “standard” product line. We are renowned for our ability to custom-design and manufacture “specialty” fixtures. Most often, these are created for very high-end projects, such as the owner’s suite in the Dallas Cowboys NFL stadium. With Graffiti, lighting designers and building owners can now access the same quality look and performance.



FIXTURE OPTIONS | 3GR23 Series

ROUND / FLANGED



ROUND / FLANGELESS



SQUARE / FLANGED



SQUARE / FLANGELESS



FIXTURE OPTIONS | 3GRF23 Series

ROUND / FLANGED



ROUND / FLANGELESS



SQUARE / FLANGED



SQUARE / FLANGELESS



FIXTURE OPTIONS | 3GRO23 Series

ROUND / FLANGED



ROUND / FLANGELESS



SQUARE / FLANGED







SQUARE / FLANGELESS



PHOTOMETRICS

SAMPLE FOR MODEL GRO-AD14-RD Series

Visit www.graffitilighting.com for further photometric data



II P L

PLUGLIGHTING.COM
INFO@PLUGLIGHTING.COM

5665 MELROSE AVENUE
STE 108 LOS ANGELES 90038

P. 323 467 5635
F. 323 467 5634

3GR23 Series

is the innovative new line
of LED lighting solutions from
Specialty Lighting Industries.



G R Series in low to medium ceiling heights typically found in residential, commercial or retail applications. 3GR23 Series fixtures are highly adjustable via hot aim-ing mechanism and hallmarked by superior light quality. The Graffiti™ fixtures provide cost effective LED light-ing solutions. As the creative spirit of its name implies, Graffiti™ systems provide all the quality SLI has grown famous for over the last 25 years, but at reduced lead times, affordable price points and innovative technologies that will liberate your creative flair.

THERMAL MANAGEMENT: Proprietary high performance aluminum black heatsink for maximum LED life

ADJUSTABLE/FIXED SPECIFICATIONS

MOUNTING - Recessed in architectural ceiling. Butterfly brackets and Hanger bars included with housing and mounting pans.

- **RM**- Open fixture for retrofit for remodel in existing ceilings
- **IC**-Housing for new construction where insulation comes in contact with fixture
- **NIC**-Housing for new construction where IC not required
- **NP**- For New construction
- **DP**- Pan for dropped ceilings
- **BP**- Pan for metal studs
- **CP**- Chicago Plenum

HOUSING - C1/C2 Fixed housing is smaller size than Lutron/EldoLED Fixed housing (see page 3 for details)*.

TRIM - One piece die cast aluminum, flanged or flangeless trim with a 1" regress bevel and overlap for flange . Available for wet locations. Accommodates up to 1" ceiling thickness as standard.

- **ZT/ZST**- for use in plaster/GWB ceilings
- **FT/FST**- for use in architectural ceilings

ELECTRICAL

- **Standard 0-10v (C1)** Dimming down to 1%
 - **TRIAC/ELV (C2)** Dimming down to 1%
 - **EldoLED 0-10v (E1)** Logarithmic Dimming down to 0.1%
 - **EldoLED Dali (E2)** Dimming down to 0.1%
 - **EldoLED 0-10v (E3)** Linear Dimming down to 0.1%
 - **Lutron Hi-lume (L2)** Hi-lume 1% (former A-Series) 2-wire Driver
 - **Lutron Hi-lume EcoSystem 1% (LTB)** Hi-lume 1% with Fade-to-Black (former H-Series) digital EcoSystem Driver
 - **Lutron Hi-lume Premier 0.1% (LTP)** Hi-lume Premier 0.1% with Fade-to-Black digital EcoSystem
 - **EM Pack** Dimming driver with emergency battery backup
- All drivers are field replaceable*

Specifier/Installer is responsible for testing & validating compatability of any control equipment used. Additional conductors may be required depending on dimming system.

LED

- **CZ- Citizen** 2700-4000K, 90+CRI
- **AD- Ambient Dim™** 3000-1900K, 97 CRI
- **XT- Xicato** 2700-4000K, 90+ CRI




LENS/OPTICS - Interchangeable reflector provides multiple beam patterns. Field-changeable optics

- **Spot (15°)**
- **Narrow (24°)**
- **Flood (38°)**
- **Wide Flood (60°)**

Optional lenses available for aperture include Solite and Veiling Acrylic. Accepts two optical accessories and an optional trim mounted lens.

FINISH - Black powder paint housing. Aper. trim available in white as standard. Can be field painted to match ceiling finish.


WARRANTY - 5 year limited on LED and driver. See website for details.

LABELS -  US tested to UL standards 1598, Dry/Damp and Wet listings. IC/Airtight,  compliant,  compliant. Chicago Plenum Available. Patent Pending. These specifications subject to change without notice. 11/19


INFORMATION- TRIM




ROUND/ FLANGED




ROUND / FLANGELESS



SQUARE / FLANGED



SQUARE / FLANGELESS



PHOTOMETRICS

*Visit website for
further photometric data
or Click Here

*LED Technology rapidly changes. Please consult factory for
latest specs and photometry.

ORDER INFO

CODE

Graffiti™ Housing

3GR23

Housing

RM = Retrofit
IC = IC
NIC = Non IC
NP = New Pan
DP = Dropped Pan
BP = Bracket Pan
CP = Chicago Plenum

Source/Wattage/Lumens/Delivered

AD14 = Ambient Dim™ / 14.5W / 1000lm / 882lm
CZ14 = Citizen / 14W / 1640lm / 1123lm
CZ20 = Citizen / 20W / 2265lm / 1424lm
XT8 = Xicato / 8W / 800lm / 616lm
XT12 = Xicato / 12W / 1055lm / 798lm
XT17 = Xicato / 17W / 1400lm / 1163lm

Type

F = Fixed C1/C2 Fixed Housing is smaller size than
A = Adjustable Lutron / Eldo LED Fixed Housing (See page 3 for Details)*

CCT

27 = 2700K
30 = 3000K
35 = 3500K
40 = 4000K
AD = 3000K-1900K* (AD14 only)

Beam

SP = Spot
NF = Narrow flood Xicato Lamp Source only available with NF and FL beam options
FL = Flood
WF = Wide flood

Driver

C1 = 0-10V dimming, 1%, 120-277v
C2 = TRIAC/ELV 2-wire, 1% 120V only (Leading/Trailing Edge)
E1 = EldoLED 0-10V Logarithmic Dim, 0.1%, 120-277v
E2 = EldoLED DALI, 0.1%, 120-277v
E3 = EldoLED 0-10V Linear Dim, 0.1%, 120-277v
L2 = Hi-lume 1% (former A-Series) 2-wire Driver, 120v only (LTEA)
LTB = Hi-lume 1% with Fade-to-Black (former H-Series) digital EcoSystem Driver, 120-277v (LDE1)
LTP = Hi-lume Premier 0.1% with Fade-to-Black digital EcoSystem, 120-277v (PEQ0)
EM** = Emergency Pack **Lutron & EldoLED require Inverter

Graffiti™ Trim

3GRT23

Shape

RD = Round
SQ = Square

Trim

FT = Flanged
ZT = Flangeless
FST* = Flanged Shower
ZST* = Flangeless Shower

*Lens Required

Finish

WHT

WHT = White

Lens

79A / 91A

91A = Solite
79A = Frosted
None

[* CLICK HERE to view Accessories for Trims.](#)

Patent Pending. These specifications subject to change without notice. 8/19

II P L

PLUGLIGHTING.COM
INFO@PLUGLIGHTING.COM


5665 MELROSE AVENUE
STE 108 LOS ANGELES 90038

P. 323 467 5635
F. 323 467 5634

INFORMATION- HOUSING

RETROFIT

For easy installation in existing ceilings.




IC/NIC/CCP


For projects requiring housings or IC rated fixtures.

1287 Hanger Bars comes standard with fixed and adjustable housing (see below for hanger bar dimensions).


ADJUSTABLE All Drivers



FIXED C1/C2 Drivers




FIXED LUTRON / ELDO Drivers




PAN

For new construction applications not requiring a housing.




OPTION - New Pan




OPTION - Dropped Pan




for use in Armstrong® T-Bar ceilings



OPTION - Bracket Pan



1287 Hanger Bar comes standard with Bracket Pan & IC/NIC
Maximum Extension: 26"



Patent Pending. These specifications subject to change without notice. 8/19

IIPL

PLUGLIGHTING.COM
INFO@PLUGLIGHTING.COM

5665 MELROSE AVENUE
STE 108 LOS ANGELES 90038

P. 323 467 5635
F. 323 467 5634