



BILO W/C

Low profile surface mount, with aluminum shade and sandblasted or clear glass. Available as ceiling or wall mount - plaster kit required.

Design by: Bruno Van Meenen

DETAILS.

FINISHES AVAILABLE IN:

BLACK

WHITE

BRONZE

ALUMINUM

SIZE: Ø3 1/8" X 1 1/4" H

LIGHT ELEMENT:

1 X 21 LED 0.2W (INCLUDED) 500MA

2300K 564 LM, 90 CRI

-OR-

2700K 587 LM, 90 CRI

REMOTE DRIVER: 1-10V DIMMABLE, 500MA

IP50 - FOR INDOOR USE

BILO W/C



II P L

PLUGLIGHTING.COM
INFO@PLUGLIGHTING.COM

5665 MELROSE AVENUE
STE 108 LOS ANGELES 90038

P. 323 467 5635
F. 323 467 5634

BILO W/C



II P L

PLUGLIGHTING.COM
INFO@PLUGLIGHTING.COM


5665 MELROSE AVENUE
STE 108 LOS ANGELES 90038

P. 323 467 5635
F. 323 467 5634

SPECS & TECHS

BILO W/C MATT


Color finishes



Material

aluminium + sandblasted glass

Dimensions



Lightsource

Bilo (for false wal)
1x 21 LED 0,14W (LED incl.) 2300K (400lm)
or 2700K (417lm) – CRI>90

aperture: Ø67 – depth: min. 70mm
required free air area: 100 x 100 x 60mm

Bilo (for concrete wall)
1x 21 LED 0,14W (LED incl.) 2300K (400lm)
or 2700K (417lm) – CRI>90

aperture: Ø67 – depth: min. 70mm
required free air area: Ø67 x 100mm

Connection

Bilo (for false wall)
remote mounted driver (350mA)
depth for driver in wall: min. 70mm
depth for driver remote: min. 60mm

Bilo (for concrete wall)
remote mounted driver (350mA)
driver must be on distance

Accessory

Plaster kit for wall




Technical specs

indoor – IP50 – class 3

BILO W/C CLEAR

SPECS & TECHS


Color finishes



Material

aluminium + transparant glass +
screen printed inner side

Dimensions



Lightsource

Bilo (for false wal)
1x 21 LED 0,14W (LED incl.)
2300K (400lm) or 2700K (417lm)
– CRI>90
aperture: Ø67 – depth: min. 70mm
required free air area: 100 x 100 x 60mm

Bilo (for concrete wall)
1x 21 LED 0,14W (LED incl.) 2300K (400lm)
or 2700K (417lm) – CRI>90
aperture: Ø67 – depth: min. 70mm
required free air area: Ø67 x 100mm

Connection

Bilo (for false wall)
remote mounted driver (350mA) depth
for driver in wall: min. 70mm
depth for driver remote: min. 60mm

Bilo (for concrete wall)
remote mounted driver (350mA) driver
must be on distance

Accessory

Plaster kit for wall



Technical specs

indoor – IP50 – class 3